

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/22/2014 : Version:

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : JOHNSEN'S THROTTLE BODY & AIR INTAKE CLEANER 10 OZ.

Product code : 4720

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Throttle Body Cleaner

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company P.O. BOX 139 Cleburne, Texas 76033 T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **Classification (GHS-US)**

Flam. Aerosol 2 H223 Compressed gas H280 Skin Irrit. 2 H315 Repr. 2 H361 STOT RE 2 H373

Full text of H-phrases: see section 16

### 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS02

 $\Diamond$ 

GHS04





Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H223 - Flammable aerosol

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) : P201 - Obtain special instructions

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking

P211 - Do not spray on an open flame or other ignition source P251 - Pressurized container: Do not pierce or burn, even after use

P260 - Do not breathe dust,fumes,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P302+P352 - If on skin: Wash with plenty of soap and water P308+P313 - If exposed or concerned: Get medical advice/attention

P314 - Get medical advice/attention if you feel unwell

P321 - Specific treatment: See section 4.1 on this label

P321 - Specific treatment: See section 4.1 on this label P332+P313 - If skin irritation occurs: Get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50  $^{\circ}$ C/122  $^{\circ}$ F P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

### 2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

25/08/2014 EN (English US) 1/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Acetone	(CAS No) 67-64-1	70 - 85	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
carbon dioxide, liquefied, under pressure	(CAS No) 124-38-9	10 - 30	Compressed gas, H280
Toluene	(CAS No) 108-88-3	5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Heptane, branched cyclic	(CAS No) 426260-76-6	3.456 - 3.6	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
heptane	(CAS No) 142-82-5	0.9 - 1.62	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest. Cough.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation

occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persist. Direct contact with the eyes is likely to be irritating.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : Shortness of breath.
Symptoms/injuries after skin contact : Causes skin irritation.

# 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

# 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns

and injuries.

# 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire

reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Aerosol Level 2.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

25/08/2014 EN (English US) 2/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill.

Methods for cleaning up : Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn,

even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing

dust,fume,gas,mist,vapor spray.

Hygiene measures : Wash affected areas thoroughly after handling.

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container

closed when not in use. Do not expose to temperatures exceeding 50  $^{\circ}\text{C}/$  122  $^{\circ}\text{F}.$  Keep in

fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

# 7.3. Specific end use(s)

Follow Label Directions.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

carbon dioxide, liquefied, under pressure (124-38-9)		
USA ACGIH	ACGIH TWA (mg/m³)	9000 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (mg/m³)	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (mg/m³)	37 mg/m³
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (mg/m³)	560
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA ACGIH	ACGIH Ceiling (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

heptane (142-82-5)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm

25/08/2014 EN (English US) 3/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

heptane (142-82-5)		
USA ACGIH	ACGIH STEL (ppm)	400 ppm
Heptane, branched cyclic (426260-76-6)		

Heptane, branched cyclic (426260-76-6)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

benzene (71-43-2)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm

acetone (67-64-1)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm

Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (mg/m³)	1200 mg/m³
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (mg/m³)	1780 mg/m³
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA ACGIH	ACGIH Ceiling (mg/m³)	0 mg/m³
USA ACGIH	ACGIH Ceiling (ppm)	3000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2400 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

# 8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.





Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Gas Appearance : Liquid.

Color : Colourless to light yellow.

Odor : Acetone odour. Solvent-like odour.

Odor threshold : 306 - 653 ppm 737 - 1574 mg/m³

pH : 7
Relative evaporation rate (butyl acetate=1) : 6
Relative evaporation rate (ether=1) : 2

Melting point : No data available Freezing point : No data available

Boiling point : 56 °C

25/08/2014 EN (English US) 4/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point : -18 °C
Auto-ignition temperature : 465 °C

Decomposition temperature : No data available Flammability (solid, gas) : No data available

Vapor pressure : 247 hPa
Vapor pressure at 50 °C : 828 hPa
Critical pressure : 47010 hPa
Relative vapor density at 20 °C : No data available

Relative density : 0.79

Solubility : Soluble in alcohols. Soluble in aromatic hydrocarbons. Soluble in ethanol. Soluble in ether.

Soluble in heptane. Soluble in toluene. Soluble in xylene.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : 0.417 mm²/s
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

9.2. Other information

Saturation concentration : 589 g/m³ VOC content : 9.6 %

# SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

#### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

# 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

# **SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

Acute toxicity : Not classified

Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)

heptane (142-82-5)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)

Heptane, branched cyclic (426260-76-6)	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)

25/08/2014 EN (English US) 5/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heptane, branched cyclic (426260-76-6)				
LC50 inhalation rat (mg/l)  103 mg/l/4h (Rat; Literature study)				
LC50 inhalation rat (ppm)				
penzene (71-43-2)  _D50 oral rat > 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg				
LD30 Oral Tat	bodyweight; Rat; Experimental value)			
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)			
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)			
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)			
acetone (67-64-1)				
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)			
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)			
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)			
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)			
Acetone (67-64-1)				
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)			
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)			
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)			
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)			
Skin corrosion/irritation : Causes skin irritation.				
	pH: 7			
Serious eye damage/irritation	: Not classified			
	pH: 7			
Respiratory or skin sensitization	: Not classified			
Germ cell mutagenicity	: Not classified			
Carcinogenicity	Not classified			
Toluene (108-88-3)				
IARC group	3			
benzene (71-43-2)				
IARC group	1			
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.			
Specific target organ toxicity (single exposure)	: Not classified			
Specific target organ toxicity (repeated exposure)	May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure			
Aspiration hazard	: Not classified			
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.			
Symptoms/injuries after inhalation	: Shortness of breath.			
Symptoms/injuries after skin contact				
SECTION 12: Ecological information				
<u> </u>				
12.1. Toxicity				

carbon dioxide, liquefied, under pressure (124-38-9)			
LC50 fish 1	35 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)		
LC50 fish 2	60 - 240 mg/l (12 h; Salmo gairdneri (Oncorhynchus mykiss); Lethal)		
Toluene (108-88-3)			
LC50 fish 1	24 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)		
EC50 Daphnia 1	84 mg/l (24 h; Daphnia magna; Locomotor effect)		
LC50 fish 2	13 mg/l (96 h; Lepomis macrochirus)		
EC50 Daphnia 2	11.5 - 19.6 mg/l (48 h; Daphnia magna)		
Threshold limit algae 1	> 400 mg/l (168 h; Scenedesmus quadricauda; Toxicity test) 105 mg/l (192 h; Microcystis aeruginosa)		
Threshold limit algae 2			
heptane (142-82-5)			
LC50 fish 1	375 mg/l (96 h; Tilapia mosambica; Nominal concentration) > 1000 mg/l (96 h)		
LC50 other aquatic organisms 1			
C50 Daphnia 1 1.5 mg/l (48 h; Daphnia magna)			

25/08/2014 EN (English US)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

heptane (142-82-5)				
LC50 fish 2	> 100 mg/l (96 h; Oncorhynchus kisutch)			
TLM fish 1	4924 mg/l (48 h; Gambusia affinis)			
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h)			
Threshold limit algae 1	> 200 mg/l (Scenedesmus quadricauda; Toxicity test)			
Threshold limit algae 2	1.5 mg/l (8 h; Algae; Photosynthesis)			
benzene (71-43-2)				
LC50 fish 1	5.3 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)			
EC50 Daphnia 1	18 mg/l (24 h; Daphnia magna)			
EC50 other aquatic organisms 1	29 mg/l (72 h; Selenastrum capricornutum)			
LC50 fish 2	15.1 mg/l (96 h; Pimephales promelas)			
EC50 Daphnia 2	10 mg/l (48 h; Daphnia magna)			
TLM fish 1	22.5 mg/l (96 h; Lepomis macrochirus; Soft water)			
TLM fish 2	32 mg/l (96 h; Pimephales promelas; Hard water)			
TLM other aquatic organisms 1	10 - 100,96 h			
Threshold limit algae 2	50 mg/l (24 h; Phaeodactylum; Photosynthesis)			
200tono (67 64 1)				
acetone (67-64-1) LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)			
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)			
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)			
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)			
TLM fish 2	> 1000 ppm (96 h; Pisces)			
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)			
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)			
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)			
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)			
	a too mg/ ( to m, o morona op.)			
Acetone (67-64-1)	0010 #/001 B: 11 1 1 1 1 1 1 1 1			
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)			
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)			
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)			
TLM fish 1 TLM fish 2	13000 ppm (96 h; Gambusia affinis; Turbulent water)			
	> 1000 ppm (96 h; Pisces)			
Threshold limit other aquatic organisms 1  Threshold limit other aquatic organisms 2	3000 mg/l (Plankton) 28 mg/l (Protozoa)			
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)			
Threshold limit algae 1 Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)			
-	3400 mg/r (40 m, Omorelia sp.)			
12.2. Persistence and degradability				
JOHNSEN'S THROTTLE BODY & AIR INTAK	CE CLEANER 10 OZ.			
Persistence and degradability	Not established.			
carbon dioxide, liquefied, under pressure (1	124-38-9)			
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.			
Biochemical oxygen demand (BOD)	Not applicable			
Chemical oxygen demand (COD)	Not applicable			
ThOD	Not applicable			
BOD (% of ThOD)	Not applicable			
Toluene (108-88-3)				
Persistence and degradability	Poadily biodagradable in water Riedagradable in the soil Lew potential for adsorption in soil			
Biochemical oxygen demand (BOD)	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.			
Chemical oxygen demand (COD)	2.15 g O <sub>2</sub> /g substance			
ThOD	2.52 g O <sub>2</sub> /g substance			
BOD (% of ThOD)	$3.13 \text{ g O}_2$ /g substance $0.69 \text{ \% ThOD}$			
heptane (142-82-5)				
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil.			
Biochemical oxygen demand (BOD)	1.92 g O <sub>2</sub> /g substance			
Chemical oxygen demand (COD)	0.06 g O <sub>2</sub> /g substance			
ThOD	3.52 g O <sub>2</sub> /g substance			
BOD (% of ThOD)	> % ThOD (5 day(s)) > 0.5			

25/08/2014 EN (English US) 7/12

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heptane, branched cyclic (426260-76-6)	Management of the state of the			
Persistence and degradability	May cause long-term adverse effects in the environment.			
benzene (71-43-2)				
Persistence and degradability	Biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Photolysis in the air.			
Biochemical oxygen demand (BOD)	2.18 g O <sub>2</sub> /g substance			
Chemical oxygen demand (COD)	2.15 g O <sub>2</sub> /g substance			
ThOD	3.10 g O <sub>2</sub> /g substance			
BOD (% of ThOD)	0.70 % ThOD			
acetone (67-64-1)				
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.			
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance			
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance			
ThOD	2.20 g O <sub>2</sub> /g substance			
BOD (% of ThOD)	(20 day(s)) 0.872			
Acetone (67-64-1)				
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.			
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance			
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance			
ThOD	2.20 g O <sub>2</sub> /g substance			
BOD (% of ThOD)	(20 day(s)) 0.872			
2.3. Bioaccumulative potential				
JOHNSEN'S THROTTLE BODY & AIR INTAK	KE CLEANER 10 OZ.			
Bioaccumulative potential	Not established.			
·	424.20.0\			
carbon dioxide, liquefied, under pressure (				
Log Pow Bioaccumulative potential	0.83 (Experimental value)  Low potential for bioaccumulation (Log Kow < 4).			
·	Low potential for bloaccumulation (Log Now < 4).			
Toluene (108-88-3)				
BCF fish 1	13.2 (Anguilla japonica)			
BCF fish 2	90 (72 h; Leuciscus idus)			
BCF other aquatic organisms 1	380 (24 h; Chlorella sp.; Fresh weight)			
BCF other aquatic organisms 2	4.2 (Mytilus edulis; Fresh weight)			
Log Pow Bioaccumulative potential	2.73 (Experimental value; Other; 20 °C)  Low potential for bioaccumulation (BCF < 500).			
Bloaccumulative potential	Low potential for bloaccumulation (BCF < 500).			
heptane (142-82-5)				
BCF other aquatic organisms 1	552			
Log Pow	4.66 (Experimental value; 4.5; Literature)			
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).			
Heptane, branched cyclic (426260-76-6)				
Bioaccumulative potential	Not established.			
benzene (71-43-2)				
BCF fish 1	19 Salmo gairdneri (Oncorhynchus mykiss)			
BCF other aquatic organisms 1	30 (24 h; Chlorella sp.; Fresh weight)			
Log Pow	2.13 (Experimental value)			
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).			
acetone (67-64-1)				
BCF fish 1	0.69 (Pisces)			
BCF other aquatic organisms 1	3			
Log Pow	-0.24 (Test data)			
Bioaccumulative potential	Not bioaccumulative.			
·				
Acetone (67-64-1)	0.60 (Picace)			
BCF fish 1	0.69 (Pisces)			
BCF other aquatic organisms 1 Log Pow	3 -0.24 (Test data)			
LOG I OW	0.27 (1031 data)			

25/08/2014 EN (English US) 8/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)			
Bioaccumulative potential	Not bioaccumulative. Not established.		
12.4. Mobility in soil			
Toluene (108-88-3)			
Surface tension	0.03 N/m (20 °C)		
heptane (142-82-5)			
Surface tension	0.020 N/m (20 °C)		
benzene (71-43-2)			
Surface tension	0.029 N/m (20 °C)		
acetone (67-64-1)			
Surface tension	0.0237 N/m		
Acetone (67-64-1)			
Surface tension	0.0237 N/m		

# 12.5. Other adverse effects

Other information : Avoid release to the environment.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under

pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1950, Aerosols, 2.1, Limited Quantity ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity

Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

### 14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosols

flammable, (each not exceeding 1 L capacity)

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Department of Transportation (DOT) Hazard

Classes

Hazard labels (DOT)

: 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

# 14.3. Additional information

Other information : No supplementary information available.

### **Overland transport**

No additional information available

# Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

25/08/2014 EN (English US) 9/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

# **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

JOHNSEN'S THROTTLE BODY & AIR INTAKE CLEANER 10 OZ.		
SARA Section 311/312 Hazard Classes Fire hazard		
Delayed (chronic) health hazard		
	Sudden release of pressure hazard	
Immediate (acute) health hazard		

Toluene (108-88-3)		
Listed on United States SARA Section 313		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes Delayed (chronic) health hazard		
	Fire hazard	
	Immediate (acute) health hazard	

	Heptane, branched cyclic (426260-76-6)  Not listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes		Fire hazard	
		Immediate (acute) health hazard	
		Delayed (chronic) health hazard	

Acetone (67-64-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard	

# 15.2. International regulations

# CANADA

JOHNSEN'S THROTTLE BODY & AIR INTAKE CLEANER 10 OZ.			
WHMIS Classification	Class B Division 5 - Flammable Aerosol		
Toluene (108-88-3)			
WHMIS Classification	Class B Division 2 - Flammable Liquid		
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects			
Heptane, branched cyclic (426260-76-6)			
WHMIS Classification	ation Class B Division 2 - Flammable Liquid		
Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
Acetone (67-64-1)			
Listed on the Canadian DSL (Domestic Sustances List)			
WHMIS Classification Class B Division 2 - Flammable Liquid			
Class D Division 2 Subdivision B - Toxic material causing other toxic effects			

### **EU-Regulations**

# Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

# Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

# Classification according to Directive 67/548/EEC or 1999/45/EC

Repr.Cat.3; R63

F; R11

25/08/2014 EN (English US) 10/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xn; R48/20 Xi; R36/38

Full text of R-phrases: see section 16

15.2.2. National regulations

# Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

#### 15.3. US State regulations

JOHNSEN'S THROTTLE BODY & AIR INTAKE CLEANER 10 OZ.()		
State or local regulations	U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)	

Acetone (67-64-1)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

#### Toluene (108-88-3)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

#### Acetone (67-64-1)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

Benzene 71-43-2

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

# **SECTION 16: Other information**

Other information : None.

Full text of H-phrases: see section 16:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Flam. Aerosol 2	Flammable aerosol Category 2
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H223	Flammable aerosol
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated
	exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

25/08/2014 EN (English US) 11/12

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



#### **HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - Technical Chemical

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

25/08/2014 EN (English US) 12/12